

PUB-NO: DE003819878A1

DOCUMENT-IDENTIFIER: DE 3819878 A1

TITLE: Gas-discharge lamp

PUBN-DATE: December 14, 1989

INVENTOR-INFORMATION:

NAME	COUNTRY
PCELIN, VLADIMIR MICHAILOVIC	SU
ARCHIPOV, JURIJ ALEKSEEVIC	SU
SACHPARUNIANC, GENNADIJ RUBENOV	SU

ASSIGNEE-INFORMATION:

NAME	COUNTRY
VNI PK I T SVETOTECHNICESKIJ I	SU

APPL-NO: DE03819878

APPL-DATE: June 10, 1988

PRIORITY-DATA: DE03819878A (June 10, 1988)

INT-CL (IPC): F21V007/09, H01J061/35

EUR-CL (EPC): H01J061/35

US-CL-CURRENT: 362/346

ABSTRACT:

CHG DATE=19990617 STATUS=O> The gas-discharge lamp has a bulb (1) in which a high-pressure gas-discharge burner (2) is accommodated in the longitudinal direction, which burner is fastened to current supply leads (6) fastened in a gas-tight manner in the base (7) of the bulb (1). At least half the entire inner surface of the bulb (1) is coated (covered) with a reflecting layer (8) in such a manner that a plane running through the edges (9) of the reflecting layer (8) is parallel to the longitudinal axis (10) of the high-pressure gas-discharge burner (2). The bulb (1) has a cross-section in which the distance between the axis (10) of the gas-discharge burner (2) and the surface of the reflecting layer (8) is constructed so as to continuously vary. The ratio of the minimum distance (r_{min}) between the axis (10) of the gas-discharge burner (2) and the surface of the reflecting layer (8) to the corresponding maximum distance (r_{max}) lies in the region of 0.6 to 1.0. <IMAGE>

